


Specification (规格): 50HP
 Shell material (外壳): carbon steel
 Tube material (管): copper
 Water connection (水接头): flanged (法兰式)
 Refrigerant (制冷剂): R407C / R22
 Evaporator temp (蒸发温度): 2'c
 Condenser temp (冷凝温度): 40'c
 Sub cool (过冷): 5 k
 Super heat (过热): 5 k
 Water inlet (进水温度): 12'c
 Water outlet (出水温度): 7'c
 Fouling factor (污垢系数): 0.000044 m²k/w

Technical Characteristics

Item	Shell Side	Tube Side
Operating Pressure (MPa)	1.0	1.4
Design Pressure (MPa)	1.0	1.4
Test Pressure (MPa)	1.25	1.61
Working Temperature (°C)	38	38
Design Temperature (°C)	38	38
Working Medium	H ₂ O	R407C / R22
Heat Transfer Area (m ²)	12.9	
Main pressure parts	Q235B, T2	
Corrosion allowance (mm)	1	
Pressure Vessel Class	/	
Design Life (Years)	20	

Symbol	Nominal Diameter	Connections	Usage
a	φ28	Brazing	Refrigerant Inlet
b	φ54	Brazing	Refrigerant Outlet
c	DN80	RF	Water Inlet
d	DN80	RF	Water Outlet
e	Rc1/2	Screw	Gas Outlet
f	Rc1/2	Screw	Gas Outlet
m	Rc1	Screw	Water Flow Meter Seat
n	Rc3/8(φ14×2)	Screw	Temperature test

Shell & Tube Dry Type Evaporator



JDEV150A10